

CATEGORY 5—TELECOMMUNICATIONS AND “INFORMATION SECURITY”

Part 1—Telecommunications

Notes:

1. The status of components, test and “production” equipment and “software” therefor which are specially designed for telecommunications equipment or systems is determined in Category 5, Part 1. (*L.N. 45 of 2010*)

N.B.:

1. For “lasers” specially designed for telecommunications equipment or systems, see 6A005.
 2. See also Category 5, Part 2 for equipment, components, and “software” performing or incorporating “information security” functions. (*L.N. 161 of 2011*)
2. “Digital computers”, related equipment or “software”, when essential for the operation and support of telecommunications equipment described in this Category, are regarded as specially designed components, provided they are the standard models customarily supplied by the manufacturer. This includes operation, administration, maintenance, engineering or billing computer systems.

5A1 SYSTEMS, EQUIPMENT AND COMPONENTS

- 5A001 (a) Any type of telecommunications equipment having any of the following characteristics, functions or features:
- (1) Specially designed to withstand transitory electronic effects or electromagnetic pulse effects, both arising from a nuclear explosion;
 - (2) Specially hardened to withstand gamma, neutron or ion radiation; *or*
 - (3) Specially designed to operate below 218 K (-55°C); (*L.N. 89 of 2021*)

Note:

(*Repealed L.N. 89 of 2021*)

- (4) Specially designed to operate above 397 K (124°C); (*L.N. 89 of 2021*)

Notes:

1. 5A001(a)(3) and 5A001(a)(4) apply only to electronic equipment.
 2. 5A001(a)(2), 5A001(a)(3) and 5A001(a)(4) do not control equipment designed or modified for use on board satellites. (*L.N. 89 of 2021*)
- (b) Telecommunications systems and equipment, and specially designed components and accessories therefor, having any of the following characteristics, functions or features: (*36 of 2000 s. 28; L.N. 254 of 2008*)
- (1) Being underwater untethered communications systems having any of the following characteristics:
 - (a) An acoustic carrier frequency outside the range from 20 kHz to 60 kHz;
 - (b) Using an electromagnetic carrier frequency below 30 kHz;
 - (c) Using electronic beam steering techniques;

- (d) Using “lasers” or light-emitting diodes (LEDs), with an output wavelength greater than 400 nm and less than 700 nm, in a “local area network”; (*L.N. 254 of 2008; L.N. 27 of 2015*)
- (2) Being radio equipment operating in the 1.5 MHz to 87.5 MHz band and having all of the following characteristics: (*L.N. 254 of 2008*)
 - (a) Automatically predicting and selecting frequencies and “total digital transfer rates” per channel to optimize the transmission; (*L.N. 254 of 2008*)
 - (b) Incorporating a linear power amplifier configuration having a capability to support multiple signals simultaneously at an output power of 1 kW or more in the frequency range of 1.5 MHz or more but less than 30 MHz, or 250 W or more in the frequency range of 30 MHz or more but not exceeding 87.5 MHz, over an “instantaneous bandwidth” of one octave or more and with an output harmonic and distortion content of better than -80 dB; (*L.N. 65 of 2004; L.N. 254 of 2008*)
- (3) Being radio equipment employing “spread spectrum” techniques, including “frequency hopping” techniques, not controlled by 5A001(b)(4), and having any of the following characteristics: (*L.N. 132 of 2001; L.N. 95 of 2006*)
 - (a) User programmable spreading codes; *or*
 - (b) A total transmitted bandwidth which is 100 or more times the bandwidth of any one information channel and in excess of 50 kHz;

Note:

5A001(b)(3)(b) does not apply to radio equipment specially designed for use with any of the following:

- (a) Civil cellular radiocommunications systems;
- (b) Fixed or mobile satellite earth stations for commercial civil telecommunications. (*L.N. 89 of 2013*)

Note:

5A001(b)(3) does not control equipment designed to operate at an output power of 1.0 Watt or less.

- (4) Being radio equipment employing ultra-wideband modulation techniques, having user programmable channelizing codes, scrambling codes or network identification codes, and having any of the following characteristics:
 - (a) A bandwidth exceeding 500 MHz; *or*
 - (b) A “fractional bandwidth” of 20% or more; (*L.N. 95 of 2006; L.N. 226 of 2009*)
- (5) Being digitally controlled radio receivers having all of the following: (*L.N. 65 of 2004*)
 - (a) More than 1 000 channels;
 - (b) A ‘channel switching time’ of less than 1 ms; (*L.N. 27 of 2015*)
 - (c) Automatic searching or scanning of a part of the electromagnetic spectrum; *and*
 - (d) Identification of the received signals or the type of transmitter;

Note:

5A001(b)(5) does not apply to radio equipment specially designed for use with civil cellular radiocommunications systems. (*L.N. 27 of 2015*)

Technical Note:

‘Channel switching time’: the time (i.e. delay) to change from one receiving frequency to another, to arrive at or within $\pm 0.05\%$ of the final specified receiving frequency. Items having a specified frequency range of less than $\pm 0.05\%$ around their centre frequency are defined to be incapable of channel frequency switching. (L.N. 27 of 2015; E.R. 6 of 2020)

- (6) Employing functions of digital “signal processing” to provide ‘voice coding’ output at rates of less than 700 bit/s; (L.N. 65 of 2004; L.N. 95 of 2006; L.N. 89 of 2021)

Technical Notes:

1. For variable rate ‘voice coding’, 5A001(b)(6) applies to the voice coding output of continuous speech.
2. For the purpose of 5A001(b)(6), ‘voice coding’ is defined as the technique to take samples of human voice and then convert these samples into a digital signal, taking into account specific characteristics of human speech. (L.N. 95 of 2006)

- (c) Optical fibres of more than 500 m in length and specified by the manufacturer as being capable of withstanding a ‘proof test’ tensile stress of 2×10^9 N/m² or more;

N.B.:

For underwater umbilical cables, see 8A002(a)(3).

Technical Note:

‘Proof Test’: on-line or off-line production screen testing that dynamically applies a prescribed tensile stress over a 0.5 to 3 m length of fibre at a running rate of 2 to 5 m/s while passing between capstans approximately 150 mm in diameter. The ambient temperature is a nominal 293 K (20°C) and relative humidity 40%. Equivalent national standards may be used for executing the proof test. (L.N. 161 of 2011)

- (d) “Electronically steerable phased array antennae” as follows:

- (1) Rated for operation above 31.8 GHz, but not exceeding 57 GHz, and having an Effective Radiated Power (ERP) equal to or greater than +20 dBm (22.15 dBm Effective Isotropic Radiated Power (EIRP));
- (2) Rated for operation above 57 GHz, but not exceeding 66 GHz, and having an ERP equal to or greater than +24 dBm (26.15 dBm EIRP);
- (3) Rated for operation above 66 GHz, but not exceeding 90 GHz, and having an ERP equal to or greater than +20 dBm (22.15 dBm EIRP);
- (4) Rated for operation above 90 GHz;

Notes:

1. 5A001(d) does not control “electronically steerable phased array antennae” for landing systems with instruments meeting ICAO standards covering microwave landing systems (MLS).
 2. 5A001(d) does not control antennae specially designed for any of the following:
 - (a) Civil cellular or WLAN radiocommunications systems;
 - (b) IEEE 802.15 or wireless HDMI;
 - (c) Fixed or mobile satellite earth stations for commercial civil telecommunications. (L.N. 89 of 2021)
- (e) Radio direction finding equipment operating at frequencies above 30 MHz and having all of the following characteristics, and specially designed components therefor:
- (1) “Instantaneous bandwidth” of 10 MHz or more; *and*

- (2) Capable of finding a line of bearing (LOB) to non-cooperating radio transmitters with a signal duration of less than 1 ms; (*L.N. 95 of 2006*)
- (f) Mobile telecommunications interception or jamming equipment, and monitoring equipment, as follows, and specially designed components for those equipments:
 - (1) Interception equipment designed for the extraction of voice or data, transmitted over the air interface;
 - (2) Interception equipment not specified in 5A001(f)(1), designed for the extraction of client device or subscriber identifiers (e.g. IMSI, TIMSI or IMEI), signalling, or other metadata transmitted over the air interface; (*E.R. 6 of 2020*)
 - (3) Jamming equipment specially designed or modified to intentionally and selectively interfere with, deny, inhibit, degrade or seduce mobile telecommunication services and performing any of the following:
 - (a) Simulate the functions of Radio Access Network (RAN) equipment;
 - (b) Detect and exploit specific characteristics of the mobile telecommunications protocol employed (e.g. GSM); (*E.R. 6 of 2020*)
 - (c) Exploit specific characteristics of the mobile telecommunications protocol employed (e.g. GSM); (*E.R. 6 of 2020*)
 - (4) Radio Frequency (RF) monitoring equipment designed or modified to identify the operation of items specified in 5A001(f)(1), 5A001(f)(2) or 5A001(f)(3);

Note:

5A001(f)(1) and 5A001(f)(2) do not apply to any of the following:

- (a) Equipment specially designed for the interception of analogue Private Mobile Radio (PMR), IEEE 802.11 WLAN;
- (b) Equipment designed for mobile telecommunications network operators;
- (c) Equipment designed for the “development” or “production” of mobile telecommunications equipment or systems.

N.B.:

1. See also the Munitions List.
2. For radio receivers, see 5A001(b)(5). (*L.N. 89 of 2013*)

- (g) Passive Coherent Location (PCL) systems or equipment, specially designed for detecting and tracking moving objects by measuring reflections of ambient radio frequency emissions, supplied by non-radar transmitters;

Technical Note:

Non-radar transmitters may include commercial radio, television or cellular telecommunications base stations.

Note:

5A001(g) does not include any of the following:

- (a) Radio-astronomical equipment;
- (b) Systems or equipment, that require any radio transmission from the target. (*L.N. 254 of 2008*)
- (h) Counter Improvised Explosive Device (IED) equipment and related equipment, as follows:
 - (1) Radio Frequency (RF) transmitting equipment, not specified in 5A001(f), designed or modified for prematurely activating or preventing the initiation of Improvised Explosive Devices;

- (2) Equipment using techniques designed to enable radio communications in the same frequency channels on which co-located equipment specified in 5A001(h)(1) is transmitting;

N.B.:

See also the Munitions List. (*L.N. 89 of 2013*)

- (i) Not used; (*L.N. 27 of 2015*)
- (j) IP network communications surveillance systems or equipment, and specially designed components for the systems or equipment, having all of the following:
- (1) Performing all of the following on a carrier class IP network (e.g. national grade IP backbone): (*E.R. 6 of 2020*)
- (a) Analysis at the application layer (e.g. Layer 7 of Open Systems Interconnection (OSI) model (ISO/IEC 7498-1));
- (b) Extraction of selected metadata and application content (e.g. voice, video, messages, attachments);
- (c) Indexing of extracted data; (*E.R. 6 of 2020*)
- (2) Being specially designed to carry out all of the following:
- (a) Execution of searches on the basis of ‘hard selectors’;
- (b) Mapping of the relational network of an individual or of a group of people;

Note:

5A001(j) does not apply to systems or equipment, specially designed for any of the following:

- (a) Marketing purpose;
- (b) Network Quality of Service (QoS);
- (c) Quality of Experience (QoE).

Technical Note:

‘Hard selectors’ data or set of data, related to an individual (e.g. family name, given name, email, street address, phone number or group affiliations). (*L.N. 27 of 2015; E.R. 6 of 2020*)

5A101 Telemetry and telecontrol equipment, including ground equipment, designed or modified for ‘missiles’;

Technical Note:

In 5A101, ‘missiles’ means complete rocket systems and “unmanned aerial vehicle” systems capable of a range exceeding 300 km.

Note:

5A101 does not control:

- (a) Equipment designed or modified for manned aircraft or satellites;
- (b) Ground based equipment designed or modified for terrestrial or marine applications;
- (c) Equipment designed for commercial, civil or safety of life (e.g. data integrity, flight safety) GNSS services.

(*L.N. 95 of 2006*)

5B1 TEST, INSPECTION AND PRODUCTION EQUIPMENT

5B001 Telecommunication test, inspection and production equipment, components and accessories, as follows: *(L.N. 89 of 2013)*

- (a) Equipment and specially designed components or accessories for the equipment, specially designed for the “development” or “production” of equipment, functions or features, specified in 5A001;

Note:

5B001(a) does not apply to optical fibre characterization equipment. *(L.N. 89 of 2013)*

- (b) Equipment and specially designed components or accessories therefor, specially designed for the “development” of any of the following telecommunications transmission or switching equipment: *(36 of 2000 s. 28; L.N. 65 of 2004)*

(1) *(Repealed L.N. 45 of 2010)*

- (2) Equipment employing a “laser” and having any of the following:

(a) A transmission wavelength exceeding 1 750 nm;

(b)-(c) *(Repealed L.N. 89 of 2021)*

(d) Employing analogue techniques and having a bandwidth exceeding 2.5 GHz;

Note:

5B001(b)(2)(d) does not apply to equipment specially designed for the “development” of commercial TV systems. *(L.N. 89 of 2013)*

(3) *(Repealed L.N. 45 of 2010)*

- (4) Radio equipment employing quadrature-amplitude-modulation (QAM) techniques above level 1 024; *(L.N. 89 of 2013; L.N. 89 of 2021)*

(5) *(Repealed L.N. 89 of 2013)*

(L.N. 65 of 2004)

5C1 MATERIALS

None;

5D1 SOFTWARE

5D001 (a) “Software” specially designed or modified for the “development”, “production” or “use” of equipment, functions or features, specified in 5A001; *(L.N. 226 of 2009)*

(b) *(Repealed L.N. 42 of 2017)*

(c) Specific “software” specially designed or modified to provide characteristics, functions or features of equipment controlled by 5A001 or 5B001; *(L.N. 95 of 2006)*

(d) “Software” specially designed or modified for the “development” of any of the following telecommunications transmission or switching equipment: *(36 of 2000 s. 28; L.N. 65 of 2004)*

(1) *(Repealed L.N. 45 of 2010)*

- (2) Equipment employing a “laser” and having any of the following:

- (a) A transmission wavelength exceeding 1 750 nm; *or*
- (b) Employing analogue techniques and having a bandwidth exceeding 2.5 GHz; *or (L.N. 45 of 2010)*

Note:

5D001(d)(2)(b) does not control “software” specially designed or modified for the “development” of commercial TV systems. *(L.N. 132 of 2001; L.N. 89 of 2021)*

- (3) *(Repealed L.N. 45 of 2010)*
- (4) Radio equipment employing quadrature-amplitude-modulation (QAM) techniques above level 1 024; *(L.N. 132 of 2001; L.N. 65 of 2004; L.N. 89 of 2021)*

5D101 “Software” specially designed or modified for the “use” of equipment controlled by 5A101; *(L.N. 65 of 2004; L.N. 95 of 2006)*

5E1 TECHNOLOGY

5E001 (a) “Technology” according to the General Technology Note for the “development”, “production” or “use” (excluding operation) of equipment, functions or features specified in 5A001 or “software” specified in 5D001(a); *(L.N. 226 of 2009)*

- (b) Specific “technologies”, as follows:
 - (1) “Required” “technology” for the “development” or “production” of telecommunications equipment specially designed to be used on board satellites;
 - (2) “Technology” for the “development” or “use” of “laser” communication techniques with the capability of automatically acquiring and tracking signals and maintaining communications through exoatmosphere or sub-surface (water) media;
 - (3) “Technology” for the “development” of digital cellular radio base station receiving equipment whose reception capabilities that allow multi-band, multi-channel, multi-mode, multi-coding algorithm or multi-protocol operation can be modified by changes in “software”; *(L.N. 65 of 2004)*
 - (4) “Technology” for the “development” of “spread spectrum” techniques, including “frequency hopping” techniques; *(L.N. 132 of 2001)*

Note:

5E001(b)(4) does not apply to “technology” for the “development” of any of the following:

- (a) Civil cellular radiocommunications systems;
- (b) Fixed or mobile satellite earth stations for commercial civil telecommunications. *(L.N. 89 of 2013)*
- (c) “Technology” according to the General Technology Note for the “development” or “production” of any of the following telecommunications transmission or switching equipment, functions or features: *(36 of 2000 s. 28; L.N. 65 of 2004)*
 - (1) *(Repealed L.N. 89 of 2021)*
 - (2) Equipment employing a “laser” and having any of the following:
 - (a) A transmission wavelength exceeding 1 750 nm;

(b)-(c) *(Repealed L.N. 89 of 2021)*

(d) Employing wavelength division multiplexing techniques of optical carriers at less than 100 GHz spacing; *or (L.N. 226 of 2009)*

(e) Employing analogue techniques and having a bandwidth exceeding 2.5 GHz;

Note:

5E001(c)(2)(e) does not control “technology” for commercial TV systems. *(L.N. 132 of 2001; L.N. 89 of 2021)*

N.B.:

For “technology” for the “development” or “production” of non-telecommunications equipment employing a laser, see 6E. *(L.N. 226 of 2009)*

(3) Equipment employing “optical switching” and having a switching time less than 1 ms; *(L.N. 45 of 2010)*

(4) Radio equipment having any of the following:

(a) Quadrature-amplitude-modulation (QAM) techniques above level 1 024; *(L.N. 65 of 2004; L.N. 254 of 2008; L.N. 89 of 2021)*

(b) Operating at input or output frequencies exceeding 31.8 GHz; *(L.N. 65 of 2004)*

Note:

5E001(c)(4)(b) does not control “technology” for equipment designed or modified for operation in any frequency band which is “allocated by the ITU” for radiocommunications services, but not for radio-determination. *(L.N. 132 of 2001; L.N. 89 of 2021)*

(c) Operating in the 1.5 MHz to 87.5 MHz band and incorporating adaptive techniques providing more than 15 dB suppression of an interfering signal; *(L.N. 254 of 2008)*

(5) *(Repealed L.N. 89 of 2013)*

(6) Mobile equipment, as follows:

(a) Operating at an optical wavelength greater than or equal to 200 nm and less than or equal to 400 nm; *and*

(b) Operating as a “local area network”; *(L.N. 226 of 2009)*

(d) “Technology” according to the General Technology Note for the “development” or “production” of “Monolithic Microwave Integrated Circuit” (“MMIC”) amplifiers specially designed for telecommunications and that are any of the following: *(L.N. 89 of 2021)*

Technical Note:

For the purposes of 5E001(d), the parameter peak saturated power output may be referred to on product data sheets as output power, saturated power output, maximum power output, peak power output, or peak envelope power output.

(1) Rated for operation at frequencies exceeding 2.7 GHz up to and including 6.8 GHz with a “fractional bandwidth” greater than 15%, and having any of the following:

(a) A peak saturated power output greater than 75 W (48.75 dBm) at any frequency exceeding 2.7 GHz up to and including 2.9 GHz;

(b) A peak saturated power output greater than 55 W (47.4 dBm) at any frequency exceeding 2.9 GHz up to and including 3.2 GHz;

(c) A peak saturated power output greater than 40 W (46 dBm) at any frequency exceeding 3.2 GHz up to and including 3.7 GHz;

- (d) A peak saturated power output greater than 20 W (43 dBm) at any frequency exceeding 3.7 GHz up to and including 6.8 GHz;
- (2) Rated for operation at frequencies exceeding 6.8 GHz up to and including 16 GHz with a “fractional bandwidth” greater than 10%, and having any of the following:
 - (a) A peak saturated power output greater than 10 W (40 dBm) at any frequency exceeding 6.8 GHz up to and including 8.5 GHz;
 - (b) A peak saturated power output greater than 5 W (37 dBm) at any frequency exceeding 8.5 GHz up to and including 16 GHz;
- (3) Rated for operation with a peak saturated power output greater than 3 W (34.77 dBm) at any frequency exceeding 16 GHz up to and including 31.8 GHz, and with a “fractional bandwidth” of greater than 10%;
- (4) Rated for operation with a peak saturated power output greater than 0.1 nW (-70 dBm) at any frequency exceeding 31.8 GHz up to and including 37 GHz;
- (5) Rated for operation with a peak saturated power output greater than 1 W (30 dBm) at any frequency exceeding 37 GHz up to and including 43.5 GHz, and with a “fractional bandwidth” of greater than 10%;
- (6) Rated for operation with a peak saturated power output greater than 31.62 mW (15 dBm) at any frequency exceeding 43.5 GHz up to and including 75 GHz, and with a “fractional bandwidth” of greater than 10%;
- (7) Rated for operation with a peak saturated power output greater than 10 mW (10 dBm) at any frequency exceeding 75 GHz up to and including 90 GHz, and with a “fractional bandwidth” of greater than 5%;
- (8) Rated for operation with a peak saturated power output greater than 0.1 nW (-70 dBm) at any frequency exceeding 90 GHz; (*L.N. 27 of 2015*)
- (e) “Technology” according to the General Technology Note for the “development” or “production” of electronic devices and circuits, specially designed for telecommunications and containing components manufactured from “superconductive” materials, specially designed for operation at temperatures below the “critical temperature” of at least one of the “superconductive” constituents, and having any of the following:
 - (1) Current switching for digital circuits using “superconductive” gates with a product of delay time per gate (in seconds) and power dissipation per gate (in watts) of less than 10^{-14} J;
 - (2) Frequency selection at all frequencies using resonant circuits with Q-values exceeding 10 000; (*L.N. 226 of 2009*)

5E101 “Technology” according to the General Technology Note for the “development”, “production” or “use” of equipment controlled by 5A101;