Director-General of Trade and Industry (Attn.: Classification Section) Strategic Trade Controls Branch Trade and Industry Department Trade and Industry Tower 3 Concorde Road, Kowloon City

Hong Kong

Fax No.: +852 3525 1526

# TRADE AND INDUSTRY DEPARTMENT NUMERICALLY CONTROLLED MACHINE TOOL QUESTIONNAIRE Classification of Numerically Controlled Machine Tools SC051 (2025/05)

(This questionnaire should be completed by the <u>manufacturer of the machine tools</u>. Supplementary sheets may be added to elaborate the answers and how the product meets the criteria)

#### Part I- Basic Information

Machine Tool	Numerical Control (NC) Unit (to be used with the Machine Tool)
Brand :	Brand :
Model Number :	Model Number :
Serial Number :	Serial Number :
Note: If the above Machine Tool <b>cannot</b> be equip	ped with electronic devices for numerical control, please

Note: If the above Machine Tool **cannot** be equipped with electronic devices for numerical control, please write "**Not Applicable**" to the Brand, Model and Serial Number of the **Numerical Control** (**NC**) **Unit**.

(Please  $\sqrt{\text{ if applicable}}$ ) Part II -**General Information (For all machine tools)** Yes No Type of Turning machine (a) machine tool Milling machine (b) Grinding machine (c) Electrical discharge machine (EDM) Others : please specify : \_\_\_\_\_ Notes to 2B001 Is the machine tool a special purpose machine tool? and 2B201 If **ves**, it is limited to the manufacture of (a) Gears; (b) Crank shafts or cam shafts; (c) Tools or cutters: (d) Extruder worms; Engraved or facetted jewellery parts; Dental prostheses. 

## Part III – Technical Information

Please select the	appropriate p	oart to answer.
-------------------	---------------	-----------------

(Please  $\sqrt{\text{ if applicable}}$ )

Yes / No

Part III.a (For turning machine only)

rari III.a	(For turning machine omy)	
2B001(a)	The machine tool has two or more axes which can be coordinated simultaneously for contouring control.	
Note 1 to 2B001(a)	The machine tool is specially designed for producing contact lenses, having <b>all</b> of the following characteristics:	
	<ul><li>(a) Machine controller limited to using ophthalmic based software for part programming data input; and</li><li>(b) No vacuum chucking.</li></ul>	
2B201	The machine tool can be equipped with electronic devices for simultaneous contouring control in two or more axes.	
2B201(c)	The machine tool is capable of machining parts with diameters greater than 35mm	
Note 2 to 2B001(a) and Note to 2B201(c)	The machine tool is a bar machine (Swissturn) limited to machining only bar feed thru.	
Note to 2D201(C)	Maximum bar diameter is equal to or less than 42 mm and there is no capability of mounting chucks.	
	(Please specify maximum bar diameter : mm)	

Part III.b (For milling machine only)

r ar t 111.0	(For mining machine only)		
2B001(b)(1)	The machine tool has three linear axes plus one rotary axis which can be coordinated simultaneously for contouring control.		
2B001(b)(2)	The machine tool has five or more axes which can be coordinated		
2B201(a)(3)	simultaneously for contouring control.		
2B001(b)(3)	The machine tool is a jig boring machine.		
2B001(b)(4)	The machine tool is a fly cutting machine, having <b>all</b> of the following characteristics:-		
	(a) Spindle run out and camming less (better) than 0.0004 mm TIR; and		
	(b) Angular deviation of slide movement (yaw, pitch and roll) less (better) than 2 seconds of arc, TIR. over 300 mm of travel.		
2B201	The machine tool can be equipped with electronic devices for simultaneous contouring control in two or more axes.		
2B201(a)(2)	The machine tool has two or more contouring rotary axes.		
Note to 2B201(a)	The machine tool's x-axis travel is greater than 2 m and the overall positioning accuracy on the x-axis is more (worse) than 30 µm.		

(Please  $\sqrt{\ }$  if applicable) Yes / No

Part III.c	(For grinding machine or	nly)

I al t III.C	(For grinding machine only)				
2B001(c)(1)(b)	The machine tool has three or four axes which can be coordinated simultaneously for contouring control.				
2B001(c)(2) 2B201(b)(3)	The machine tool has five or more axes which can be coordinated simultaneously for contouring control.				
2B201	The machine tool can be equipped with electronic devices for simultaneous contouring control in two or more axes.				
2B201(b)(2)	The machine tool has two or more contouring rotary axes.				
Note to 2B001(c)	1. The machine tool is a cylindrical external, internal, and external-internal grinding machine having <b>all</b> the following characteristics:-				
	<ul><li>(a) Limited to cylindrical grinding; and</li><li>(b) Limited to a maximum workpiece capacity of 150 mm outside diameter or length.</li></ul>				
	2. The machine tool is designed specially as jig grinder that does not have a z-axis or a w-axis.				
	3. The machine tool is a surface grinder.				
Note to 2B201(b)	<ul> <li>(a) The machine tool is a cylindrical external, internal, and external-internal grinding machines having all of the following characteristics:</li> <li>(1) Limited to a maximum workpiece capacity of 150 mm outside diameter or length; and</li> <li>(2) Axes limited to x, z and c.</li> </ul>				
	(b) The machine is a jig grinder that does not have a z-axis or a w-axis with an overall positioning accuracy less (better) than 4 $\mu$ m according to ISO 230/2 (1988) or national equivalents.				

# Part III.d (Compound rotary tables and tilting spindles specially designed for turning, milling or grinding machine)

2B008(c)(2)	Compound rotary tables having two rotary axes designed to be coordinated simultaneously for contouring control.	
2B008(d)(2)	Tilting spindles designed to be coordinated simultaneously for contouring control.	

Part III.e Unidirectional Positioning Repeatability and Positioning Accuracy (For turning machine, milling machine and grinding machine)

No. of Linear Axis	No. of Rotary Axis	Maxir	num Travel	Unidirectional positioning repeatability in accordance with ISO 230/2 (2014)		Positioning accuracy with all compensations available in accordance with ISO 230/2 (1988)		
( )	( )			ISO 230/2 (2014)	National Equivalents Please specify:	ISO 230/2 (1988)	National Equivalents Please specify:	
		X-axis	(mm)	(mm)	(mm)	(mm)	(mm)	
		Y-axis	(mm)	(mm)	(mm)	(mm)	(mm)	
		Z-axis	(mm)	(mm)	(mm)	(mm)	(mm)	
	Others:			(mm)	(mm)	(mm)	(mm)	
				(mm)	(mm)	(mm)	(mm)	
				(mm)	(mm)	(mm)	(mm)	
				(mm)	(mm)	(mm)	(mm)	
				(mm)	(mm)	(mm)	(mm)	

	` ′	` /	` ,		` ′	`
Others:		(mm)	(mm)		(mm)	(m
		(mm)	(mm)		(mm)	(m
		(mm)	(mm)		(mm)	(m
		(mm)	(mm)		(mm)	(m
		(mm)	(mm)		(mm)	(m
Part III.f (2B001(d)	For electrical discharge ma  The machine tool is a wire  The machine tool is a non-v	type EDM.	aly)	(Please	√ if ap Yes	pplicable) / No
	The machine tool has two o coordinated simultaneously (Please specify the number	for contouring c	ontrol.			
Part IV -	Numerical Control (NC) U	nit				
2D002	The software residing in the coordinating simultaneously contouring control.		_	of		
Note 1 to 2D002	The software residing in the designed or modified for the specified in <b>Part I</b> .		-	•		
Part V -	Licence Information					
The Machine Tool as specified in <b>Part I</b> requires an export licence from the exporting country.						
A copy of export licence of the Machine Tool as specified in <b>Part I</b> is attached.						
		<u> </u>				

\_\_\_\_\_\_

### Part VI – Declaration

I am the **manufacturer** of the Machine Tool as specified in **Part I**. I declare to the best of my knowledge and belief the information given above is true and correct.

Name of Signatory:	
	(in block letters)
Position of Signatory in the	
Company:	
Company name :	
Signature & Company chop :	
Date:	
Date	

Important Note:

The data collected in this form will be kept in confidence. They may however be disclosed to other government departments, or to third parties in Hong Kong or elsewhere, if such disclosure is necessary to facilitate consideration of the related application, is in the interests of the trade in Hong Kong, is authorised or required by the law; or if explicit consent to such disclosure is given by the applicant/data subject.

For further information concerning the handling of personal data by the Department, please refer to a relevant Note issued by the Department on the subject, copy of which is obtainable from the Strategic Trade Controls Branch, 16/F, Trade and Industry Tower, 3 Concorde Road, Kowloon City, Hong Kong.